

CTS-Series Mini Slim-Line Vertical Contact Toaster

Introducing Prince Castle's CTS Mini Slim-Line Vertical Contact Toaster. A revolutionary new design that increases toasting versatility, maximizes space savings, and provides perfect caramelization with the convenience of vertical contact toasting.

Prince Castle's unique two-level platen design allows the operators to toast thicker bun crowns and thinner bun heels at the same time. The variable speed motor is adjustable to allow for toasting speeds up to 2200 buns per hour.

The Prince Castle Advantage:

- · Slim-Line design saves up to 30% more counter space
- · Adjustable toast times from 9-40 seconds to customize products
- Digital display and electronic controls make for precise and repeatable settings
- · Available in wire and silicone belt (at 120V)
- Simple to remove conveyor makes cleaning guick and easy
- Dual compression adjustment knobs allow for maximum product flexibility
- · Accommodates all buns up to 5.5" in diameter
- Heat Shield for cooler surfaces ensuring safer operation
- Durable stainless steel construction makes the product easy-to-clean and maintain

All Prince Castle Slim-Line Toasters come equipped with our Release Sheet Kit consisting of a Stainless Steel Clamp and Two Non-Stick Teflon Sheets to protect against bun sticking.







QUALITY TASTE STARTS WITH QUALITY EQUIPMENT.

Striving for Greatness.

At Prince Castle, we are all about the journey. For 60 years, we've been dedicated to helping improve restaurant operations so they can consistently serve a great-tasting product quickly and safely. We have learned that no matter how good your menu is, it always starts with your equipment.

| Model Number | Description | Volts | Hertz | Watts | Amps | Plug |
|--------------|------------------------|---------|-------|-------|-----------|------------|
| CTS-W | Toaster (Wire Belt) | 120 | 50/60 | 1500 | 12.5 | NEMA 5-I5P |
| CTS-WCE | Toaster (Wire Belt) | 220-240 | 50/60 | 1500 | 6.82-6.25 | CEE7 7 |
| CTS-WS | Toaster (Silicon Belt) | 120 | 50/60 | 1500 | 12.5 | NEMA 5-I5P |

Product Dimensions + Weight

Width 20.25" (51 4cm) Depth 7.25" (18 4cm) Height: 22.0" (55 9cm)

Unit Weight: 65.0 lbs (29 5kg)

Shipping

Width 24.5" (62 2cm) Depth 13 0" (33 0cm) Height: 27.0" (68 5cm)

Shipping Weight: 68.0 lbs (31.0kg)

Warranty

I Year Parts and Labor

Temperature Range

350°-550° F

Optional Accessories

Butter Wheel

Certifications





CE - Pending

Conveyor Options





Silicone Belt

Wire Belt

Conveyor design provides optional belt configurations to include wire and silicone to meet any sandwich bun toasting application.